

# Winsonic<sup>®</sup>

LCD TV is a digital television system that displays digital video on an LCD (Liquid Crystal Display) and supports digital/analog video broadcasting (cable, satellite, terrestrial), broadband connection, personal video recording (PVR), interactive internet, and wireless connectivity.

L1041T



Breathtaking clarity, stunningly vibrant colors, rich acoustical depth, and seamless multimedia integration make Winsonic a leader in LCD TV technology. Its sleek, elegant design and range of sizes ensure you'll enjoy its bright, crisp picture from virtually any viewing angle; the thrill of optimized game mode; true-to-life surround sound;

Winsonic LCD TVs are designed using advanced imaging technology to provide a stunning visual experience. Elegant, flat-panel designs conserve space while you enjoy your favorite movies, television shows, and video games in style and comfort. Winsonic puts the excitement of Xtreme entertainment in your living room, den, or home theater with a breathtaking video and audio experience.

Winsonic's high-performance widescreen LCD TV combines HIGH-PERFORMANCE WITH HIGH STYLE to deliver impressive TV. Immerse yourself in the vibrant colors and lifelike images of this high-definition TV. Fast video response, high brightness and contrast ratio produce crystal clear, blur-free moving images. Multiple video and audio connections, including HDMI, allow you to connect HD set top boxes, DVD players, game consoles and more to build a complete high definition home entertainment system that your neighbors will envy.

# Specifications

**LCD with resolution up to 800 X 600**

**Multi-scan function supports SVGA, VGA, XVGA text mode**

**Auto-recognition of input signal**

**Panel or wallmount**

**Supports VESA arm, Desktop Stand**

**Glass surface: Black Anti-Glare low reflection coating**

## L1041T

Panel	Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD panel		
	Aspect Ratio / Size	4 : 3 / 10.4" viewable diagonal area		
	Glass Surface	Black Anti-Glare, low reflection coating		
	Pixel numbers / Colors	800(H) x 600(V) / 262 K		
	Pixel Pitch	0.264 (H) x 0.264 (V) mm		
	Active Area	211.2(H) x 158.4(V) mm		
	Light Source	Long life, 50,000 hrs (typ)		
	Brignthess / Contrast	350 cd/m <sup>2</sup> (typ) , 400 : 1		
	Viewing Angle	Horizontal & Vertical 140° (typ) (- 70° ~ + 70°)		
Response Time	≤ 25 ms			
Input Sources	TV System	NTSC or PAL / SECAM ( 181 Channels)		
	Video System	NTSC / PAL / SECAM		
	PC System	Signal	Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)	
		Sync	Composite Sync, Separate Sync, Sync On Green	
	Frequency	F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz		
	Resolution	800 x 600@60/70/75 Hz		
		640 x 480@60 / 70 / 75 Hz		
Recommended	800 x 600@60 Hz			
Input Terminals	Audio System	Stereo 2W X 2 (Built-In Speaker)		
	TV Tunner	TV Tunner x 1		
Output Terminal	S-Video	4 Pin Dim S-Connector x 1		
	Composite Video(AV)	RCA Jack X 1		
	Component Audio	RCA Jack X 2		
	PC Signal	15 Pin Female D-Sub x 1		
	PC Audio	Stereo Headphone Jack x 1		
	Headphone	Stereo Jack x 1		
Control	Front Panel (5 Keys)	Men/Exit , Select , Channel-Up , Channel-Down , Power		
	Remote Controller	Infrared		
Convenient Features	Auto Calibration			
	Back Light Adjustment			
	Wall Mount Ready	VESA 75 X 75(mm)		
Power power Rating (Support DPMS)	Input Voltage	Universal / Auto-Sensing, 90 to 260VAC, 50 / 60 Hz		
	- Operation	40 watt		
	- Stand-By	< 5 watt		
	- Off	< 5 watt		
Operating Condition	Temperature	0°C - 40°C (32°F - 104°F)		
	Humidity	10% - 90% (no condensation)		
Storage Condition	Temperature	- 20°C - 60°C (- 4°F - 140°F)		
	Humidity	10% - 90% (no condensation)		
Dimensions	Physical	Without Base : (W x H x D) 266 x 204 x 80 (mm)		