

Winsonic[®]

LCD TV is a digital television system that displays digital video on an LCD (Liquid Crystal Display) and supports digital/analog video broadcasting (cable, satellite, terrestrial), broadband connection, personal video recording (PVR), interactive internet, and wireless connectivity.



L3211T

Breathtaking clarity, stunningly vibrant colors, rich acoustical depth, and seamless multimedia integration make Winsonic a leader in LCD TV technology. Its sleek, elegant design and range of sizes ensure you'll enjoy its bright, crisp picture from virtually any viewing angle; the thrill of optimized game mode; true-to-life surround sound;

Winsonic LCD TVs are designed using advanced imaging technology to provide a stunning visual experience. Elegant, flat-panel designs conserve space while you enjoy your favorite movies, television shows, and video games in style and comfort. Winsonic puts the excitement of Xtreme entertainment in your living room, den, or home theater with a breathtaking video and audio experience.

Winsonic's high-performance widescreen LCD TV combines HIGH-PERFORMANCE WITH HIGH STYLE to deliver impressive TV. Immerse yourself in the vibrant colors and lifelike images of this high-definition TV. Fast video response, high brightness and contrast ratio produce crystal clear, blur-free moving images. Multiple video and audio connections, including HDMI, allow you to connect HD set top boxes, DVD players, game consoles and more to build a complete high definition home entertainment system that your neighbors will envy.

Specifications

L3211T

LCD with resolution up to 1366 X 768

Multi-scan function supports SVGA, VGA, XGA text mode

Auto-recognition of input signal

Panel or wallmount

Supports VESA arm, Desktop Stand

Glass surface: Black Anti-Glare low reflection coating

Panel	Cell Type Aspect Ratio / Size Glass Surface Pixel numbers / Colors Pixel Pitch Active Area Light Source Brignthness / Contrast Viewing Angle Response Time	Color active matrix TFT (Thin-Film-Transistor) LCD panel 16 : 9 / 31.5" viewable diagonal area Black Anti-Glare, low reflection coating 1366(H) x 768(V) / 16.7 million 0.51 (H) x 0.51 (V) mm 697.68(H) x 392.26(V) mm Long life, 60,000 hrs (typ) 550 cd/m ² (typ) , 1000 : 1 Horizontal & Vertical 170° (typ) (- 88° ~ + 88°) ≤ 8ms
Input Sources	TV System Video System PC System Audio System	NTSC / PAL / SECAM (181 Channels) NTSC / PAL / SECAM Signal Analog RGB (0.7/1.0 V _{p-p} , 75 ohms) Digital (HDMI) Sync Composite Sync, Separate Sync, Sync On Green Frequency F _h : 30 - 82Khz , F _v : 50 -75Hz Resolution 1366 x 768@60 / 70 / 75 Hz 1024 x 768@60 / 70 / 75 Hz 800 x 600@60 / 70 / 75 Hz Recommended 1366 x 768@60HZ 15W x 2 (Built-In Speaker)
Input Terminals	TV Tunner S-Video Composite Video(AV) Component Video Component Audio HDMI PC Signal (Analog RGB) PC Audio	TV Tunner x 1 4 Pin Dim S-Connector x 1 RCA Jack x 1 RCA Jack x 3 (Y _P P _R) RCA Jack x 2 (Audio _R & Audio _L) 15 Pin Female D-Sub x 1 Stereo Headphone Jack x 1
Output Terminal Control	Headphone Front Panel (7 Keys) Remote Controller	Stereo Jack x 1 Source , Men/Exit , Channel-Up , Channel-Down + (Up & Inc)(Volume) , -(Down & Dec)(Volume) , Power Infrared
Convenient Features	HDTV Ready Auto Calibration Back Light Adjustment Wall Mount Ready	1080i / 720P / 480P Supported
Optional Features	NTSC TV System PAL & SECAM TV System	MTS (Multi-Channel Television Sound) CC (Closed Caption) V-Chip Nicam Teletex Scart Connector
Power power Rating (Support DPMS)	Input Voltage - Operation - Stand-By - Off	Universal / Auto-Sensing, 90 to 260VAC, 50 / 60 Hz 140 watt < 10 watt < 10 watt
Operating Condition	Temperature Humidity	0°C ~ 40°C (32°F ~ 104°F) 10% ~ 90% (no condensation)
Storage Condition	Temperature Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) 10% ~ 90% (no condensation)
Dimensions	Physical Carton	With Base Without Base
Container Loaded	20 ft / 40 ft / 40ft HQ	112 / 234 / NA sets